

REAR WICKER EXTENSION KIT INSTALLATION INSTRUCTIONS

1. Tape off rear spoiler with low stick masking tape so the spoiler does not get scratched while working on it
2. From either corner of the spoiler measure and find the center point of the spoiler. mark with a pencil on tape
3. Align wicker extension up against spoiler. align bottom edge with edge of spoiler. this will be the lowest point of adjustment of the wicker once installed. This is best achieved with 2 people.
4. Making sure bottom edge and centered, mark with a pencil all 6 mounting location slots. be very careful to not move wicker as you are marking slots
5. Set aside wicker extension and mark center of each slot and from the top edge of the slot mark down 1/4". this is the center point of where you will drill holes for Nutsert
6. At each center point drill a 1/16" pilot hole first. once pilot holes are drilled. Drill a 3/8" hole at each 6 locations. Be very careful while drilling these holes. Do not drill too deep and drill straight.
7. Insert Nutsert with nut tool attached into 3/8" hole. holding Nutsert into hole with thumb and 7/16" open end wrench tighten nut closest to the Nutsert with a second 7/16" open end wrench clockwise approximately 4 complete rotations. Nut tool is marked black on one side of nut to identify position.
8. Once Nutsert is tightened turn nut counter-clockwise a half turn to loosen tool and remove
9. Repeat this on all 6 Nutserts and then remove masking tape

***** DO not over tighten mounting screws or Nutsert could twist and become loose. the blue lock tight is applied so screws do not need to be very tight to hold on wicker *****



Visit our Facebook Page for more details and videos